

Specifications and Options for ATR 41-45 Sign and Traffic

GENERAL SPECIFICATIONS

(Based on 40" Frame)

	ATR-41	ATR-45
Horizontal Reach	26'-2" (8.0 m)	30'-2" (9.2 m)
Max Platform Capacity	500 lbs (272 kg)	500 lbs (272 kg)
Platform Rotation	180°	180°
Max Jib Capacity	1000 lbs (454 kg)	1000 lbs (454 kg)

HEIGHTS WITH STANDARD PEDESTAL

Bottom of Platform Height	36'-4" (11.1 m)	40'-4" (12.3 m)
Working Height	41'-4" (12.6 m)	45'-4" (13.8 m)
Stowed Travel Height	10'-6" (3.2 m)	10'-6" (3.2 m)

BOOM ACTION

Outer/Inner Boom Articulation	-25 to + 85°	-25 to + 85°
Inner Boom Extension	79" (2.0 m)	103" (2.6 m)
Lower Boom Articulation	0 to 87°	0 to 87°
Rotation	360°	360°

VEHICLE REQUIREMENTS

Cab to Axle (minimum)	60" (1.5 m)	84" (2.14 m)
GVWR	17,500 lbs (7,940 kg)	17,500 lbs (7,940 kg)

NOTE:

- Specifications may vary without prior notification.
- Required GVWR can vary significantly with chassis, lift mounting location, service body, accessories, and desired payload.

OPTIONS

- Auxiliary Outriggers
- Second Set of Tool Power Ports
- Lifting Eye
- Emergency Power
- Various Pedestal Heights
- Hydraulic Jib/Winch (reduces platform capacity 100 lbs)
- Unitrol H.R.

