



4850 Orange Avenue

Ft. Pierce, Florida 34947

Tel: 772-461-6056 1-800-226-5056 Fax: 772-464-2716

www.stamm-mfg.com - E-Mail: johnnystm@stamm-mfg.com

July 15, 2010

DAKOTA SERVICE BODY SPECIFICATIONS

1. Dimensions: 108" long x 40" high by 94" wide with 20" deep compartments and a 54" wide load area.
2. Constructed using 14-16 ga. galvanized body paneling, 12 ga. treadplate galvanized floor and tailshelf, 18 ga. galvanized double panel doors, stainless steel rods, hinge blocks and high gloss stainless steel lockable paddle handles with automotive type rotary latches. Vertical doors have spring "hold open" door holders and horizontal doors have chains. All doors have automotive type bulb seal.
3. Compartmentation includes:
 - Curbside: Transverse shelf through body;
Top shelf 10" down from compartment top;
Two (2) 4" high material drawers with adjustable dividers on 6-inch centers, drawers each include mounting on pipe rollers to pull out to curbside half length.
 - Horizontal: One (1) removable shelf with adjustable divider on 6-inch centers;
 - Rear Vertical: One (1) adjustable shelf with adjustable dividers on 6-inch center;
 - Streetside: First vertical same as curbside compartment;
Bottom shelf to pull out to street side half length;
 - Horizontal: One (1) removable shelf with tapered dividers on 6-inch centers;
Adjustable dividers installed in compartment bottom on 6-inch centers;
 - Rear Vertical: Two (2) adjustable shelves with adjustable dividers on 6-inch center;
4. 16" Tailshelf with (2) 1" curved pipe aluminum hand rails in board and (2) 1" x 20" high cone holders (removable) on outside corners.
5. Six (6) tie downs in floor 6" from wall, three (3) on each side centered.
6. Three (3) ratch straps 8' long 1500 lb. strength.
7. Round tube for Collins lights on right side curbside rear vertical on left side of panel at edge with thumb lock for light not to turn.
8. Tool storage box with lift up aluminum step plate lid, gas filled shocks, rubber seal and mounted on top of Streetside compartment. Dimensions 72" L x 18" W x 14" H hasp latch, cannot be bolted through top, weld on or bolt through sides.
9. Right side compartment top covered with gripstrut and acts as part of the entry ladder to the platform. Includes required hand rails and GS steps to platform.
10. 8" HD gripstrut bumper full width under platform tailshelf.
11. 6-pin plug for Collins light mounted in rear bumper.

12. 6-pin Berg plug trailer towing receptacle, 2 5/16" ball, pintle hitch combo, adjustable shank Buyers Products model (BH825K) and two (2) O-rings for safety chains.
13. Primed and finish painted with two coats of Confident Yellow to match cab. Inside of compartments are also primed.
14. Platform floor and body floor coated with non-slip Bed Lining (spray on HD type).
15. LED lighting and reflectors to meet FMVSS including rubber mounted 4" Stop-Tail-Turn and clearance. Standard back up and license plate light to be protected. Lights are recessed in tailshelf for protection. All wiring harness must be in metal conduit, any exposed area and inside of body also.
16. Three (3) hooks on compartment wall street side in floor area for ladder.
17. Exhaust pipe to be moved from curbside to street side of truck at rear.
18. Compartments to get rope lighting LED type and switch in cab wired to junction box.
19. Install mud flaps on body.
20. One (1) Whelen light bar model FX2AAAA with one (1) FXALF10, two (2) FXTLSID, four (4) FLDA, one (1) 46-0783728-12, and one (1) MKEZ38.
21. Four (4) Whelen strobe lights Model 500 series – 50C0000ZR, two (2) rear facing high in body panels and two (2) front facing in chassis grill with lighted cab switch.

One (1) Motorola radio XTL 764-870 MHZ 35 Watt, Model XTL 1500

Option: G809AT in log 3600 band

Antenna G335AT

Speaker B18CL

COST \$3,000.00

PRICE

Approx. \$ 75,079.00

FOB Ft. Pierce, FL

Price to Paint Cab – Open

If you have any questions, please do not hesitate to contact me.

Sincerely,

Albert E. Patterson

AEP:ss